

Specification for Axminster (AX)

3ply – 9row

Construction:	Woven Axminster – Electronic Jacquard
Yarn Content:	80% Premium Grade Virgin Wool / 20% Nylon
Twist Coefficient:	3 ply 740 tex
Dye Method:	Skein Dyed
Weft:	Polypropylene
Warp:	Cotton / PET Polyester
Secondary Backing:	SBR Latex (fire retardant)

	Imperial	Metric
Yarn Ply:	3 ply – 3/42	3 ply – 4050/3
Rows per Inch:	9 per inch	35.43 per DM
Pitch per Inch:	7 per inch	27.56 per DM
Pile Height:	0.280"	7.0mm
Total Thickness:	0.350"	8.5mm
Effective Pile Weight:	30 oz/yd ²	1015 gr/m ²
Total Pile Weight:	44 oz/yd ²	1490 gr/m ²
Width:	13' 2"	4m

Performance

Color Fastness (light) :	ISO 105 - B02 ≥ 5
Color Fastness (rubbing):	ISO 105 - X12 ≥ 4
Tuft Withdrawal Force:	ISO 4919 ≥ 10N
TARR:	ISO 10361 ≥ 3
Anti-Static:	ISO 6356 ≥ 2Kv
Flammability:	ASTM E - 648 Radiant Flux: Class 1 ≥ 0.5 W/cm ² BS4790: Pass EN 13501 - 1: Cfl – s1

All specifications subject to normal manufacturing tolerances.

Encore Hospitality flooring products are to be installed in full accordance with Encore's installation instructions and standard trade practices. A program of regular cleaning and maintenance is vital for retaining a high appearance level. Installation plus Care & Maintenance manuals can be downloaded at www.encorehospitalitycarpet.com