

# Specification for CP-Colorpoint 36oz

---

Construction:	Colorpoint
Yarn Content:	Zeftron Nylon
Dye Method:	Solution Dyed
Gauge:	1/10th
Width:	12'0" (up to 15ft available)
Yarn Weight Tufted:	36 oz.
Stitch Rate:	12 SPI
Pile Heights:	approx. - low - .175" / high - .315"
Primary Backing:	Woven Polypropylene
Secondary Backing:	Woven Polypropylene
Pattern Repeat:	TBD

## Performance

---

Flame Resistance:	Passes DOC FF-1-70
Static Control:	Less than 3.5 KV
Flooring Radiant Panel:	Class 1 (ASTM 648)
Smoke Density:	Less than .450 (ASTM E622)
Soil Resistance:	Commercial Anti-Soil Protection
Stain Resistance:	Commercial Stain Protection

## Warranties

---

Wear:	10 Year Limited
-------	-----------------

All specifications subject to normal manufacturing tolerances.

Encore Hospitality flooring products are to be installed in full accordance with Encore's installation instructions and standard trade practices. A program of regular cleaning and maintenance is vital for retaining a high appearance level. Installation plus Care & Maintenance manuals can be downloaded at [www.encorehospitalitycarpet.com](http://www.encorehospitalitycarpet.com)