

# Specification for Hand-tufted (HT)

## HT450

---

<b>Construction:</b>	Hand-tufted	ISO 2424
<b>Yarn Content:</b>	100% New Zealand Wool   Moth proof treated	ISO 2424
<b>Dye Method:</b>	Skein Dyed	
<b>Yarns:</b>	1/82 Dewsberry Count   Z-twist	
<b>Size &amp; Shape:</b>	Custom	
<b>Total Weight:</b>	3625 g/m <sup>2</sup>   107 oz/yard <sup>2</sup>	ISO 8543
<b>Total Pile Weight:</b>	2439 g/m <sup>2</sup>   72 oz/yard <sup>2</sup>	ISO 2424
<b>Number of Tufts:</b>	520 /dm <sup>2</sup>   43477 /yard <sup>2</sup>	ISO 1763
<b>Primary Backing:</b>	Cotton Canvas   65% cotton/35% polyester	ISO 2424
<b>Secondary Backing:</b>	Cotton Mesh   Natural Rubber Latex	ISO 2424
<b>Effective Pile Thickness:</b>	85 mm   0.33 in	ISO 1766

### Performance

---

**Flame Resistance:** Passes BS 4790

All specifications subject to normal manufacturing tolerances.

Encore Hospitality flooring products are to be installed in full accordance with Encore's installation instructions and standard trade practices. A program of regular cleaning and maintenance is vital for retaining a high appearance level. Installation plus Care & Maintenance manuals can be downloaded at [www.encorehospitalitycarpet.com](http://www.encorehospitalitycarpet.com)