

# Specification for CP-Colorpoint 32oz

---

|                     |                                      |
|---------------------|--------------------------------------|
| Construction:       | Colorpoint                           |
| Yarn Content:       | Zeftron Nylon                        |
| Dye Method:         | Solution Dyed                        |
| Gauge:              | 1/10th                               |
| Width:              | 12'0" (up to 15ft available)         |
| Yarn Weight Tufted: | 32 oz.                               |
| Stitch Rate:        | 12 SPI                               |
| Pile Heights:       | approx. - low - .175" / high - .315" |
| Primary Backing:    | Woven Polypropylene                  |
| Secondary Backing:  | Woven Polypropylene                  |
| Pattern Repeat:     | TBD                                  |

## Performance

---

|                         |                                 |
|-------------------------|---------------------------------|
| Flame Resistance:       | Passes DOC FF-1-70              |
| Static Control:         | Less than 3.5 KV                |
| Flooring Radiant Panel: | Class 1 (ASTM 648)              |
| Smoke Density:          | Less than .450 (ASTM E622)      |
| Soil Resistance:        | Commercial Anti-Soil Protection |
| Stain Resistance:       | Commercial Stain Protection     |

## Warranties

---

|       |                 |
|-------|-----------------|
| Wear: | 10 Year Limited |
|-------|-----------------|

All specifications subject to normal manufacturing tolerances.

Encore Hospitality flooring products are to be installed in full accordance with Encore's installation instructions and standard trade practices. A program of regular cleaning and maintenance is vital for retaining a high appearance level. Installation plus Care & Maintenance manuals can be downloaded at [www.encorehospitalitycarpet.com](http://www.encorehospitalitycarpet.com)