

## Specification for Colorpoint (CP) 42oz

Construction:	Colorpoint
Yarn Content:	Zeftron Nylon
Dye Method:	Solution Dyed
Gauge:	1/10th
Width:	12'0" (up to 15ft available)
Yarn Weight Tufted:	42 oz
Stitch Rate:	12 SPI
Pile Heights:	approx. - low - .175 / high - .315
Primary Backing:	Woven Polypropylene
Secondary Backing:	Contract Unitary
Pattern Repeat:	TBD

---

### Performance

Flame Resistance:	Passes DOC FF-1-70
Static Control:	Less than 3.5 KV
Flooring Radiant Panel:	Class 1 (ASTM 648)
Smoke Density:	Less than .450 (ASTM E622)
Soil Resistance:	Available
Stain Resistance:	Available

---

### Warranties

Wear:	10 Year Limited
Static:	Lifetime Limited
Colorfastness:	Lifetime Limited

All specifications subject to normal manufacturing tolerances.

Encore Hospitality flooring products are to be installed in full accordance with Encore's installation instructions and standard trade practices. A program of regular cleaning and maintenance is vital for retaining a high appearance level. Installation plus Care & Maintenance manuals can be downloaded at [www.encorehospitalitycarpet.com](http://www.encorehospitalitycarpet.com)