

## Specification for En-Pointe Tableau 36oz Cut Pile

Construction:	Tableau
Yarn Content:	Zeftron Nylon Solution
Dye Method:	Dyed
Gauge:	1/13th
Width:	15'
Yarn Weight Tufted:	36 oz
Stitch Rate:	13 SPI
Primary Backing:	Woven Polypropylene
Secondary Backing:	Contract Unitary
Pile Height:	.250" Approx.
Total Thickness:	.375" Approx.
Pattern Repeat:	TBD

---

### Performance

Flame Resistance:	Passes DOC FF-1-70
Static Control:	Less than 3.5 KV
Flooring Radiant Panel:	Class 1 (ASTM 648)
Smoke Density:	Less than .450 (ASTM E622) Commercial
Soil Resistance:	Anti-Soil Protection W/UPCHARGE
Stain Resistance:	Commercial Stain Protection W/UPCHARGE

---

### Warranties

Wear:	10 Year Limited
-------	-----------------

All specifications subject to normal manufacturing tolerances.

Encore Hospitality flooring products are to be installed in full accordance with Encore's installation instructions and standard trade practices. A program of regular cleaning and maintenance is vital for retaining a high appearance level. Installation plus Care & Maintenance manuals can be downloaded at [www.encorehospitalitycarpet.com](http://www.encorehospitalitycarpet.com)