

Specification for En-Pointe Tableau (TB) 48oz Cut Pile

Construction: Tableau

Yarn Content: Chromanyl Solution Dyed Nylon

Dye Method: Solution Dyed

Gauge: 1/13th
Width: 12' | 15'
Yarn Weight Tufted: 48 oz
Stitch Rate: 13 SPI

Primary Backing: Woven Polypropylene Secondary Backing: Contract Unitary approx 0.250"

Total Thickness: standard backing approx 0.380"

cushion backing approx 0.470"

Pattern Repeat: TBD

Performance

Flame Resistance: Passes DOC FF-1-70 Static Control: Less than 3.5 KV Flooring Radiant Panel: Class 1 (ASTM 648)

Smoke Density: Less than .450 (ASTM E622)

Soil Resistance: Commercial Anti-Soil Protection w/ upcharge Stain Resistance: Commercial Stain Protection w/ upcharge

Warranties

Wear: 10 Year Limited

Tufted pile weight is based on material post production; pattern and shear amounts may alter final tufted pile weight.

All specifications subject to normal manufacturing tolerances.

Encore Hospitality flooring products are to be installed in full accordance with Encore's installation instructions and standard trade practices. A program of regular cleaning and maintenance is vital for retaining a high appearance level. Installation plus Care & Maintenance manuals can be downloaded at www.encorecarpet.net