

## Specification for Hand-Tufted (HT) HT650

Construction:	Hand-Tufted	ISO 2424
Yarn Content:	100% New Zealand Wool	ISO 2424
	Moth proof treated	
Dye Method:	Skein Dyed	
Yarns:	1/82 Dewsberry Count   Z-twist	
Size & Shape:	Custom	
Total Weight:	5285 g/m <sup>2</sup>   156oz/yrd <sup>2</sup>	ISO 8543
Total Pile Weight:	3524 g/m <sup>2</sup>   104 oz/yrd <sup>2</sup>	ISO 2424
Total Thickness:	14.5 mm	
Number of Tufts:	312 /dm <sup>2</sup>   26086 oz/yrd <sup>2</sup>	ISO 1763
Primary Backing:	Cotton Canvas	ISO 2424
	65% cotton / 35% polyester	
Secondary Backing:	Cotton Mesh	ISO 2424
	Natural Rubber Latex	
Effective Pile Thickness:	85 mm   0.33 in	ISO 1766

---

### Performance

Flame Resistance: Passes BS 4790

All specifications subject to normal manufacturing tolerances.

Encore Hospitality flooring products are to be installed in full accordance with Encore's installation instructions and standard trade practices. A program of regular cleaning and maintenance is vital for retaining a high appearance level. Installation plus Care & Maintenance manuals can be downloaded at [www.encorehospitalitycarpet.com](http://www.encorehospitalitycarpet.com)