

## Specification for Double Stick Fiber Pad (DS32) 32oz

Weight:	32 oz
Thickness:	.315"
Density:	8.9 lbs./cu. ft.
Roll Width:	6'   12'
Roll Length:	60'   60'

---

### Performance

Tensile Strength:	
Length:	205
Width:	238
Pill Test:	Pass
FHA Type/Class:	H 1 & 2
Radiant Panel-ASTME 648:	Class 1
R-Rating:	2.05
Content:	100% Synthetic Recycled Fiber (70% Pre Consumer Recycled Material) (30% Post Consumer Recycled Material)

ENCORE warrants that its manufactured products are free from any defects in workmanship and material, will provide satisfactory service and a lively and resilient foundation for the life of the carpet under which it is originally installed over flat, smooth, hard surfaces on or above grade. The synthetic fiber is mold, moth, mildew, and odor resistant and can be used below grade.

ENCORE as a sole and exclusive remedy, will replace, without charge, any manufactured product which does not render satisfactory service in normal use F.O.B. manufacturing plant. This warranty does not include the cost or installation. No liability will be assumed for any consequential damage, loss or expense.

Installation plus Care & Maintenance manuals can be downloaded at [www.encorehospitalitycarpet.com](http://www.encorehospitalitycarpet.com).